

Troubleshooting SAML

Last Modified on 06/04/2026 9:15 am IDT

 This article is designated for administrators.

About

This guide helps you diagnose and resolve common SAML-related login problems in the legacy Video Portal. It's intended for admins who already completed their SAML integration and are testing authentication for the first time.

Before you start

Make sure:

- You're familiar with SAML 2.0 basics.
- Your IdP configuration is complete.
- You can access the legacy Video Portal's Configuration Management console.

Verifying the Integration

Log in to the legacy Video Portal using SAML. If the integration is working, you should see your user ID in the top-right corner.

What else should you verify?

Look at the `userId` / user name on the upper right corner, and in legacy Video Portal Configuration Management console (`/admin/user-list`).

- Does the `userId` that you received match the expected one?
 - If not, make sure that the `userId` attribute is released in the SAML response.
 - Make sure that the `userId` attribute is mapped correctly.
- Did you release and map any additional attributes?
 - If so, make sure that the user has the expected additional information (first name, last name, email address).
- Was the user assigned the expected role?
 - A user should get the default role that you set when you configured the SAML module.
 - If you also configured role mapping (assignment of legacy Video Portal role per the value(s) of attribute(s)), check if the user received the expected role. If not,

double check that the attribute is released, and that the attribute name and expected value are matching the ones in the SAML response. Values are case sensitive.

In some cases, login may fail. From an end user perspective, this might look like an “application error” page on the MediaSpace side, or a redirect loop.



If the error occurs on the IdP side, or before the browser is redirected back to MediaSpace, please check the error on the IdP side.

When login fails, please use web tracking tools (SAML Tracer for FireFox, Fiddler, Charles, and Chrome dev tools are a few examples that can be used for this task), and look at the http response headers of `https://{your_KMS_UR}/user/authenticate`.

Error codes and description

The following table provides a list of the error code IDs, message and a description.

Error Code	Description	Suggested Actions
1001	Failed to get data entry (failed to load the SAML configuration).	Clear the MediaSpace cache, refresh the admin and try again. Contact customer care if the issue persists.
1002	METADATA_FOR_ENTITY_NOT_FOUND You accessed MediaSpace or redirected the user to the wrong domain.	Please make sure to access MediaSpace via the domain that you defined in spMetadata -> host.

Error Code	Description	Suggested Actions
1003	INVALID_MESSAGE_ASSERTION_CONSUMER_SERVICE_ENDPOINT Your IdP returned an invalid SAML response.	Please check the SAML response, and proceed accordingly.
1004	MISSING_ISSUER_ASSERTION_CONSUMER_SERVICE_ENDPOINT Missing <saml:Issuer> in the SAML response as posted to the AssertionConsumerService.	Configure your IdP to release <saml:Issuer>
1005	MULTIPLE_ASSERTIONS_IN_RESPONSE More than one assertion in received response.	
1006	RESPONSE_STATUS_NOT_SUCCESS	Check the SAML Response, check the IdP logs to see what made it fail the SAML response. SAML response must be of status: Success for the login to succeed.
1007	RESPONSE_EMPTY_USER_ID SAML response contains empty user ID or no name ID in the SAML response subject.	Please add an IdP rule to release a nameId attribute. You can adjust the requested nameId format in the SAML request per your IdP's preference.

Error Code	Description	Suggested Actions
1010	Exception other	Look for the error message in the header and proceed accordingly.